



Previous Name: Shell Torcula Oils

Shell Air Tool S2 A 150

- *Reliable Protection*
- *Mist Lubrication*

Pneumatic Tool and Rock Drill Oils

Shell Air Tool S2 A has been developed to meet the special lubrication requirements of pneumatic tools, including percussion type pneumatic tools subjected to the most severe conditions. They are designed to maintain high oil film strength and effectively lubricate even the most demanding requirements of pneumatic drill impact mechanisms as well as providing excellent mist lubrication of general purpose air tools.

DESIGNED TO MEET CHALLENGES

Performance, Features & Benefits

■ Reliable wear & corrosion protection

Shell Air Tool Oil S2 A has been developed to provide excellent lubricity and anti-wear properties to protect percussion tools including rock drills operating under severe conditions.

It also provides high levels of corrosion protection even under severe water wash conditions.

The high oil film strength provides for excellent load carrying performance and increased drill life.

■ Maintaining system efficiency

To ensure efficient lubrication under the full range of operation, Shell Air Tool Oil S2 A has good low temperature fluidity at low temperatures to provide consistent lubrication and to resist oil build-up in areas cooled by rapid air expansion.

Shell Air Tool Oil S2 A has excellent emulsability enabling lubrication in a wet environment.

■ Percussive pneumatic tools

Suitable for a wide range of mobile percussive pneumatic tools such as those used in rock drilling, mining and construction activities (e.g. jack hammers, sinkers and other air operated tools).

■ Oil mist lubrication applications

Shell Air Tool Oil can also be used in applications requiring mist lubrication, such as air tool installations commonly found in manufacturing.

■ Other applications

May be used in certain gear and bearing lubrication systems subject to water ingress.

Specifications, Approvals & Recommendations

■ ISO 6743-11 Types PAC and PBC

For additional questions and listing of equipment approvals and recommendations, contact your local Shell Technical Helpdesk or the OEM Approvals website.

Compatibility & Miscibility

■ Seal & Paint Compatibility

Shell Air Tool Oil S2 A is compatible with seal materials and paints normally specified for use with mineral oils.

Main Applications



Typical Physical Characteristics

Properties			Method	Shell Air Tool Oils S2 A
ISO Viscosity Grade			ISO 3448	150
Kinematic Viscosity	@40°C	mm ² /s	ISO 3104	150
Kinematic Viscosity	@100°C	mm ² /s	ISO 3104	15.1
Viscosity Index			ISO 2909	101
Flash Point		°C	ISO 2592 (COC)	246
Pour Point		°C	ISO 3016	-24
Density	@15°C	kg/m ³	ISO 12185	887

These characteristics are typical of current production. While future production will conform to Shell's specification, variations in these characteristics may occur.

Health, Safety & Environment

- Guidance on Health and Safety is available on the appropriate Material Safety Data Sheet, which can be obtained from <http://www.epc.Shell.com/>
- **Protect the Environment**
Take used oil to an authorized collection point. Do not discharge into drains, soil or water.

Additional Information

- **Advice**
Product recommendations on applications not listed here may be obtained from your Shell representative.